


Aluminum



DIMENSIONS

RATED CAPACITY	H	H1	L	L1	L2	L3	L4	W	T
kg/mm									
0.2	33.0	6.0	110.0	86.0	7.0	5.0	18.0	5.0	M3 Depth12
0.3-0.6	33.0	6.0	110.0	86.0	7.0	5.0	18.0	9.0	M3 Depth12
0.75-6	33.0	6.0	110.0	86.0	7.0	5.0	18.0	10.0	M3 Depth12
lb/inches (conversion of above dimensions)									
0.44	1.30	0.24	4.33	3.39	0.28	0.20	0.71	0.20	M3 Depth0.47
0.66-1.32	1.30	0.24	4.33	3.39	0.28	0.20	0.71	0.35	M3 Depth0.47
1.65-13.23	1.30	0.24	4.33	3.39	0.28	0.20	0.71	0.39	M3 Depth0.47

SPECIFICATIONS

Full Scale Output	1.0 mV/V $\pm 20\%$	Recommended Excitation	10V (15V Maximum)
Zero Balance	± 0.02 mV/V	Reference Max. Platform Size	Capacity < 1kg: 200 $\times$ 200 mm Capacity ≥ 1 kg: 230 $\times$ 230 mm
Non-linearity	Cap. < 1kg: $< \pm 0.023\%$; Cap. ≥ 1 kg: $< \pm 0.017\%$	Insulation Resistance	> 2 [50V DC] G Ω
Repeatability	Cap. < 1kg: $< \pm 0.023\%$; Cap. ≥ 1 kg: $< \pm 0.017\%$	Nominal Temperature Range	-10°C to 40°C / 14°F to 104°F
Hysteresis Error	Cap. < 1kg: $< \pm 0.023\%$; Cap. ≥ 1 kg: $< \pm 0.017\%$	Safe Overload	150% of full scale
Creep in 30 min.	Cap. < 1kg: $< \pm 0.050\%$; Cap. ≥ 1 kg: $< \pm 0.023\%$	Breaking Overload	300% of full scale
Input Resistance	415 $\Omega \pm 15$	Seal Type / IP Rating	Environmentally Sealed / IP66
Output Resistance	350 $\Omega \pm 3$	Cable Color Code	Exc+ Red Exc- Black Sig+ Green Sig- White Shield Bare
Element Material	Aluminum		

PART NUMBER*

Rated Capacity	Part No.	Weight (kg) Approx.
200g	108PA-200g	0.1
300g	108PA-300g	0.1
600g	108PA-600g	0.1
1kg	108PA-1kg	0.1
2kg	108PA-2kg	0.1
3kg	108PA-3kg	0.1
6kg	108PA-6kg	0.1

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

INTERCHANGEABLE REFERENCE

Manufacturer	Model
HBM	SPL
Vishay TedeA-Huntleigh	1004

OIML 1kg-6kg: OIML C3