



Aluminum



Features:

- Wing beam-self compensates for overturning moment
Suited for composite, durable plastic or lightweight aluminum scale bases
Ideal for picture frame style infant incubator scales, where scale center is hollow for X-Ray access
- Low profile-provides ability for scales of roughly 25mm height, in various rectangular shapes / sizes
- Current Calibrated: No J-Box w/Trim Pot required
Direct corner replacement w/o need for re-calibration
- Rated output of 0.9mV/V±0.1%: Pre-derated for ease of planar beam selection for scale capacity
EX: For a 60kg scale capacity-simply use 4x202WA-15kg's
Enables full weight capacity to roll up on scale edge w/o fear of overload



Optional: with a 4 conductor ribbon cable and Female connector: 104257-4 + Crimp:1-104481-0 (interchange with AMP#103957-4). Part number needs to add suffix-02 for this option.

RATED CAPACITY	DIMENSIONS			H	H1	L	L1	W	W1	W2
	C1	C2	C3							
lb/inches										
12.5-18.75	0.18	0.17	-	0.10	-	2.50	1.25	2.50	2.09	1.25
25	0.18	0.18	-	0.11	-	2.50	1.25	2.50	2.09	1.25
37.5	0.18	0.18	-	0.14	-	2.50	1.25	2.50	2.09	1.25
50	0.18	0.18	-	0.16	-	2.50	1.25	2.50	2.09	1.25
100	0.18	0.18	-	0.25	-	2.50	1.25	2.50	2.09	1.25
200	0.18	0.18	0.28	0.31	0.16	2.50	1.25	2.50	2.09	1.25
kg/mm										
100	4.6	4.6	7.1	8.3	4.0	63.5	31.8	63.5	53.1	31.8
200	4.6	4.6	7.1	11.7	5.0	63.5	31.8	63.5	53.1	31.8
300	4.6	4.6	7.1	14.3	5.0	63.5	31.8	63.5	53.1	31.8


SPECIFICATIONS

Full Scale Output	0.9 mV/V ± 0.1%	Element Material	Aluminum, Clear Anodized
Calibration in mV/V/Ω	± 0.05%	Recommended Excitation	10V (15V Maximum)
Zero Balance	± 0.02 mV/V	Insulation Resistance	>2 [50V DC] GΩ
Non-linearity	< ± 0.017%	Nominal Temperature Range	-10°C to 40°C / 14°F to 104°F
Repeatability	< ± 0.017%	Safe Overload	150% of full scale
Hysteresis Error	< ± 0.017%	Breaking Overload	300% of full scale
Creep in 30 min.	< ± 0.030%	Seal Type / IP Rating	Environmentally Sealed / IP65
Input Resistance	1204 Ω ± 5	Cable Color Code	Exc+ Green Exc- Black Sig+ White Sig- Red
Output Resistance	1000 Ω ± 10		

PART NUMBER*

Rated Capacity	Free end cable	With ribbon cable & connector	Weight (kg) Approx.
12.5lb.....	202WA-12.5lb.....	202WA-12.5lb-02.....	0.1
18.75lb....	202WA-18.75lb....	202WA-18.75lb-02.....	0.1
25lb	202WA-25lb.....	202WA-25lb-02.....	0.1
37.5lb.....	202WA-37.5lb.....	202WA-37.5lb-02.....	0.1
50lb.....	202WA-50lb.....	202WA-50lb-02.....	0.2
100lb.....	202WA-100lb.....	202WA-100lb-02.....	0.2
200lb.....	202WA-200lb.....	202WA-200lb-02.....	0.2
100kg.....	202WA-100kg.....	202WA-100kg-02.....	0.2
200kg.....	202WA-200kg.....	202WA-200kg-02.....	0.2
300kg.....	202WA-300kg.....	202WA-300kg-02.....	0.2

INSTALLATION DRAWING



* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the “Information”) in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD’s knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

⚠ WARNING: Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.