

Thermal Receipt Printer, ABS



Features:

- Direct thermal print
- ABS enclosure material
- USB or RS-232 interface
- User friendly plug and play
- Low-noise thermal printing
- Easy paper roll installation
- Easy paper jam clearance
- Easy maintenance for tasks such as head cleaning

INDICATORS

SPECIFICATIONS			
Printing Method	Direct Thermal	Paper Thickness	0.06 - 0.08 mm
Printing Speed	90 mm / s	Character Size	ANK, Font A: 12 x 24 dots Font B: 9 x 17 dots
Roll Paper	Paper width: 57.5 ± 0.5mm	Barcode	UPC-A / UPC-E / JAN13 (EAN13) / JAN8 (EAN8) / CODE39 / ITF / CODABAR / CODE93 / CODE128 / QR code
Column Capacity	384 dots / line	Working Environment	Temperature (32 °F - 113 °F / 0 °C - 45 °C), Humidity (10 - 80%)
Command	Compatible with ESC / POS	Storage Environment	Temperature (14 °F - 140 °F / -10 °C - 60 °C), Humidity (10 - 90%)
Interface (optional)	Serial / Parallel / USB / LAN	Drivers	Win 9X / Win 2000 / Win 2003 / Win XP / Win 7 / Win 8 / Win 8.1 / Linux
Auto Cutter	Full		
Reliability	Printing head life: 50 km		
Adaptor Input Voltage	AC 110 V / 220 V, 50 - 60Hz		
Power Supply	DC 12 V / 2.6 A		
Printer Input Voltage	DC 12 V / 2.6 A		
Cash Drawer Control	DC 12 V / 1 A		

PART NUMBER

Part No.	Shipping Weight Approx. (kg)
PS805-C.....	1.0

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the “Information”) in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD’s knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

⚠ WARNING: Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.