


Cable Connector



SPECIFICATIONS					
Part Number	CCP5-S	CCP5-S1	CCP5-L	CCP5-L1	CCP7-L
Rated Current	30A				15A
Contact Diameter	φ3mm×5				φ2mm×7
Contact Resistance	1mΩ				2.5mΩ
Wire Size mm ² / AWG	≤ 4.17/11				≤ 2/14
Termination	Screw	Solder	Screw	Solder	Solder
Cable Outer Diameter	φ4.5-7mm		φ7-12mm		
Shell Material	PC, Nylon66, fire resistance: V-0				
Insert Material	PPS, max temperature 260°C				
Contact Material	Brass with gold plating				
Rated Voltage (AC)	500V				
Test Voltage/min (AC)	1500V				
Mating Cycle	> 500				
Insulation Resistance	2000MΩ				
Working Temperature	-40°C to 85°C / -40°F to 185°F				
Protection Class	IP68				

PART NUMBER

Part No.	Contacts	Termination	Weight Approx. (kg)
CCP5-S.....	5.....	screw.....	0.06
CCP5-S1.....	5.....	solder.....	0.06
CCP5-L.....	5.....	screw.....	0.06
CCP5-L1.....	5.....	solder.....	0.06
CCP7-L.....	7.....	solder.....	0.06

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

 **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.