



CE RoHS

### DIMENSIONS

RATED CAPACITY	H	L	L1	L2	L3	L4	W	T
<b>kg/mm</b>								
7-60	30.2	139.7	32.0	88.7	19.1	6.4	23.9	1/4-20UNC-2B Depth15
<b>lb/inches</b> (conversion of above dimensions)								
15.4-132.3	1.19	5.50	1.26	3.49	0.75	0.25	0.94	1/4-20UNC-2B Depth0.6

### SPECIFICATIONS

<b>Full Scale Output</b>	2.0 ± 10% mV/V	<b>Recommended Excitation</b>	10V (15V Maximum)
<b>Zero Balance</b>	±0.02 mV/V	<b>Reference Max. Platform Size</b>	400 × 400 mm
<b>Non-linearity</b>	< ± 0.017%	<b>Insulation Resistance</b>	>2 [ 50V DC ] GΩ
<b>Repeatability</b>	< ± 0.017%	<b>Compensated Temperature Range</b>	-10°C to 50°C / 14°F to 122°F
<b>Hysteresis Error</b>	< ± 0.017%	<b>Safe Overload</b>	150% of full scale
<b>Creep in 30 min.</b>	< ± 0.023%	<b>Breaking Overload</b>	300% of full scale
<b>Input Resistance</b>	385 Ω ± 15	<b>Seal Type / IP Rating</b>	Environmentally Sealed / IP66
<b>Output Resistance</b>	350 Ω ± 3	<b>Cable Color Code</b>	Exc+ Red    Exc- Black Sig+ Green    Sig- White    Shield Bare
<b>Element Material</b>	2Cr13 Stainless Steel		

### PART NUMBER

Rated Capacity	Part No.	Shipping Weight (kg) Approx.
7kg.....	108TSSL-7kg-YZ.....	0.5
10kg.....	108TSSL-10kg-YZ.....	0.5
15kg.....	108TSSL-15kg-YZ.....	0.5
30kg.....	108TSSL-30kg-YZ.....	0.6
60kg.....	108TSSL-60kg-YZ.....	0.6

### INTERCHANGEABLE PRODUCTS

Manufacturer	Model
HBM.....	PWS
Rice Lake.....	RL1380

SINGLE POINTS