

## FSP Series

### FEATURES

- Hot dip galvanized & ultra heavy duty steel construction
- Extra thickness -- 6mm thick deck plate with checkered safety tread
- Extra thickness -- 6mm thick rigid steel channel frame construction
- Symmetrical grid channel frame
- Pre-corner error adjustment
- Threaded eyebolt holes for easy lifting (eyebolts included)
- Installed with:
  - \* 4 high accuracy IP67 alloy steel shear beam load cells (563YH) (OIML MAA C6, Y=8,500 and NTEP 1:5000 Class III, Multiple Cell)
  - \* 4 swivel mild steel feet with removable rubber base (AMF - ¾)
  - \* 1 IP67 aluminum 4-way junction box (J04EA)
  - \* 2 eyebolts
  - \* Level bubble
- NTEP approved



<b>Part#</b>	<b>FSP4X4-10Klb-GH</b>
<b>Capacity</b>	10000 lb
<b>Division</b>	2 lb
<b>Platform Size</b>	48 in X 48 in / 121.9 cm X 121.9 cm
<b>Platform Material</b>	Mild Steel
<b>Net Weight</b>	419 lb / 190 kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104 °F

\*Dimensions and specifications are subject to change without notice.