



CE RoHS

Designed & made for extreme high resolution balance.

### DIMENSIONS

RATED CAPACITY	C	H	L	L1	W	W1	W2
kg/mm							
250	6.6	8.3	63.5	31.8	63.5	50.2	31.8
lb/inches (conversion of above dimensions)							
551.2	0.26	0.33	2.50	1.25	2.50	1.98	1.25

### SPECIFICATIONS

Full Scale Output	0.9 mV/V ± 0.1%	Recommended Excitation	10V (15V Maximum)
Calibration in mV/V/Ω	± 0.05%	Insulation Resistance	>2 [ 50V DC ] GΩ
Zero Balance	± 0.02 mV/V	Nominal Temperature Range	-10°C to 50°C / 14°F to 122°F
Non-linearity	< ± 0.01%	Safe Overload	150% of full scale
Repeatability	< ± 0.01%	Breaking Overload	300% of full scale
Hysteresis Error	< ± 0.01%	Seal Type / IP Rating	Environmentally Sealed / IP65
Creep in 30 min.	< ± 0.01%	Cable Color Code	Exc+ Red      Exc- Black
Input Resistance	1204Ω ± 5		Sig+ Green    Sig- White
Output Resistance	1000Ω ± 10		
Element Material	Alloy Steel		

### PART NUMBER

Rated Capacity	Part No.	Shipping Weight (kg) Approx.
250kg.....	202WH-250kg.....	0.2

### INSTALLATION DRAWING

