



\*Shackles & indicators optional

## OCSD Series

### FEATURES

- Fast resolution switching
- 25mm 5 digits LCD display w/ backlight
- Peak Hold function
- Accurate Class up to 0.1%
- 2 Programmable set-point
- Unit switch: kg / lb / t / N / kN
- Auto power-off function
- Matches with standard shackles
- Must have one of the indicators to calibrate and / or change parameters

### OPTION

- Wireless Indicator (P180)
- Wireless Handheld Indicator (P380)
- Indicator / Printer (P580)
- Galvanized shackle hook (SBX)
- Scoreboard (BD)

| Model                     | OCSD   | OCSD   |
|---------------------------|--|--|
| <b>Type</b>               | Dynamometer                                  | Dynamometer                                  |
| <b>Accuracy Class</b>     | Following OIML R76, Class III, NOT certified | Following OIML R76, Class III, NOT certified |
| <b>Enclosure</b>          | Aluminum                                     | Alloy Steel                                  |
| <b>Display</b>            | 25mm LCD w/ Backlight                        | 25mm LCD w/ Backlight                        |
| <b>Capacity Available</b> | 1/2/3/5t                                     | 10/20/30/50/100/200t                         |
| <b>Battery Life</b>       | 50Hours                                      | 50Hours                                      |
| <b>Battery</b>            | 3 x AA                                       | 3 x AA                                       |

| Rated Capacity | Division    | H           | L           | W          | H1          | W1        | C           | N.W.        | SBX (shackle) |
|----------------|-------------|-------------|-------------|------------|-------------|-----------|-------------|-------------|---------------|
| 1t/2Klb        | 0.5kg/1lb   | 245mm/9.6"  | 112mm/4.4"  | 37mm/1.5"  | 190mm/7.5"  | 25mm/1.0" | 20.5mm/0.8" | 1.6kg/4lb   | 3.25t         |
| 2t/4Klb        | 1kg/2lb     | 260mm/10.2" | 123mm/4.8"  | 37mm/1.5"  | 195mm/7.7"  | 30mm/1.2" | 24mm/0.9"   | 2.1kg/5lb   | 4.75t         |
| 3t/6Klb        | 1kg/2lb     | 260mm/10.2" | 123mm/4.8"  | 37mm/1.5"  | 195mm/7.7"  | 30mm/1.2" | 24mm/0.9"   | 2.1kg/5lb   | 4.75t         |
| 5t/10Klb       | 2kg/5lb     | 285mm/11.2" | 123mm/4.8"  | 54mm/2.1"  | 210mm/8.3"  | 34mm/1.3" | 27mm/1.1"   | 2.7kg/6lb   | 6.5t          |
| 10t/20Klb      | 5kg/10lb    | 320mm/12.6" | 120mm/4.7"  | 54mm/2.1"  | 230mm/9.1"  | -         | 41mm/1.6"   | 10.4kg/23lb | 13.5t         |
| 20t/40Klb      | 10kg/20lb   | 375mm/14.8" | 128mm/5.0"  | 71mm/2.8"  | 260mm/10.2" | -         | 54mm/2.1"   | 17.8kg/39lb | 25t           |
| 30t/60Klb      | 10kg/20lb   | 420mm/16.5" | 138mm/5.4"  | 79mm/3.1"  | 280mm/11.0" | -         | 60mm/2.4"   | 25kg/55lb   | 35t           |
| 50t/100Klb     | 20kg/50lb   | 465mm/18.3" | 150mm/5.9"  | 101mm/4.0" | 305mm/12.0" | -         | 74mm/2.9"   | 39kg/86lb   | 55t           |
| 100t/200Klb    | 50kg/100lb  | 570mm/22.4" | 190mm/7.5"  | 129mm/5.1" | 366mm/14.4" | -         | 99mm/3.9"   | 91kg/201lb  | 120t          |
| 200t/400Klb    | 100kg/200lb | 720mm/28.3" | 265mm/10.4" | 180mm/7.1" | 440mm/17.3" | -         | 135mm/5.3"  | 210kg/463lb | Call          |

\*Dimensions and specifications are subject to change without notice.