



CE RoHS

DIMENSIONS

RATED CAPACITY	C	H	H1	H2	H3	W	T
t/mm							
0.5-1	70.0	101.3	33.5	51.8	76.0-99.0	77.0	M12
2	70.0	119.8	50.0	51.8	78.0-116.0	77.0	M16
Klb/inches							
1-2.5	2.76	3.99	1.32	1.96	2.99-3.90	3.03	1/2-20 UNF

SPECIFICATIONS

Full Scale Output	2.0 mV/V \pm 0.25%	Recommended Excitation	10V (15V Maximum)
Zero Balance	\pm 0.02 mV/V	Insulation Resistance	>2 [50V DC] G Ω
Non-linearity	< \pm 0.050%	Compensated Temperature Range	-10°C to 50°C / 14°F to 122°F
Repeatability	< \pm 0.030%	Safe Overload	150% of full scale
Hysteresis Error	< \pm 0.050%	Breaking Overload	300% of full scale
Creep in 30 min.	< \pm 0.030%	Seal Type / IP Rating	Welded Seal / IP67
Input Resistance	380 Ω \pm 20	Cable Color Code	Exc+ Red Exc- Black
Output Resistance	350 Ω \pm 3		Sig+ Green Sig- White
Element Material	Alloy Steel		Shield Bare

PART NUMBER

Rated Capacity	Part No.	Weight (kg) Approx.
500kg.....	106MH-F-500kg.....	1.0
1t.....	106MH-F-1t.....	1.0
2t.....	106MH-F-2t.....	1.0
1Klb.....	106MH-F-1Klb.....	1.0
2.5Klb.....	106MH-F-2.5Klb.....	1.0

WEIGH MODULE

Model	Page
106MHM1.....	137