

Thermal Receipt Printer, ABS



Features:

- Low-noise thermal printing
- Easy paper jam clearance
- Easy maintenance for tasks such as head cleaning
- Compact and elegant design
- Anti-water splash, anti-dust design
- Fit big paper roll
- Low power consumption

SPECIFICATIONS

Print Method	Direct Thermal	Print Speed	Max. 100mm/s
Resolution	203dpi(8 dots/mm)	Standard	Paper out Detector
RAM	20KB	Operating	-5~50°C; 25~80% R.H
Flash	2MB	Storage	-40~60°C; ≤93% R.H(40°C)
Paper Roll Width	58mm	Dimension	196mm(L) X 124mm(W) X 128mm(H)
Paper Roll Diameter	Max. 83mm(O.D.)	Driver	Windows XP / Vista / 7 / 8 / 8.1 / 10; POSReady; Linux; OPOS
Paper Thickness	0.056~0.13mm	Linear Barcodes	UPC-A, UPC-E, ENA-8, ENA-13, CODE 39, ITF, CODEBAR, CODE 128, CODE 93
Paper Loading	Top Easy Paper Loading		
Print Width	Max. 48mm		

PART NUMBER

Part No.	Weight (kg) Approx.
PS805-B.....	1.0

INDICATORS