

Thermal Receipt Printer, ABS



Features:

- User friendly plug and play
- Direct thermal print
- USB or RS-232 interface
- Low-noise thermal printing
- Easy paper roll installation
- Easy paper jam clearance
- Easy maintenance for tasks such as head cleaning
- ABS enclosure material

SPECIFICATIONS

Print	Method	Direct Thermal	Interface	USB, RS232
	Resolution	203dpi(8 dots/mm)	Sensor	Paper out detector
	Print Speed	up to 100mm/s	Power Supply	Input: AC 100V-240V, 50/60Hz
	Print Width	up to 48mm (1.89 inch)		Output: DC 12V, 2A
Memory	RAM	20KB	Driver	Windows XP / Vista / 7 / 8 / 8.1 / 10; POSReady; Linux; OPOS
	Flash	2MB		
Paper	Paper Type	thermal receipt paper	Linear Barcodes	UPC-A, UPC-E, ENA-8, ENA-13, CODE 39, ITF, CODEBAR, CODE 128, CODE 93
	Paper Width	58mm (2.28 inch)		
	Paper Thickness	0.056~0.13mm	Operating Environment	-5~50°C; 25~80% R.H
	Paper Roll Diameter	Max. 83mm(O.D.)	Storage Environment	-40~60°C; ≤93% R.H(40°C)
	Paper Loading	From top, drop-in	Overall Dimensions	196 X124X128(mm, L x W x H)

PART NUMBER

Part No.	Weight (kg) Approx.
PS805-B.....	1.0

INDICATORS