

## FSP Series

### FEATURES

- Hot dip galvanized mild steel construction
- 5mm thick deck plate with checkered safety tread
- Rigid steel channel frame construction
- Symmetrical grid channel frame
- Pre-corner error adjustment
- Threaded eyebolt holes for easy lifting (eyebolts included)
- Installed with:
  - \*4 high accuracy IP67 alloy steel shear beam load cells (563YH) (OIML MAA C6, Y=8,500 and NTEP 1:5000 Class III, Multiple Cell)
  - \*4 swivel mild steel feet with removable rubber base (AMF-F-1/2)
  - \*1 IP67 aluminum 4-way junction box (J04EA-16)
  - \*2 eyebolts
  - \*Level bubble



\*NTEP Approval for 5Klb: FSP-4X4-GI



MEASUREMENT CANADA

\*Measurement Canada Approval for 5Klb:FSP-4X4-GI

<b>Part#</b>	<b>FSP4X4-5Klb-GI</b>
<b>Capacity</b>	5000lb
<b>Division</b>	1lb
<b>Platform Size</b>	48in X 48in/ 121.9cm X 121.9cm
<b>Platform Material</b>	Mild Steel
<b>Net Weight</b>	304lb / 138kg
<b>Operating Temp.</b>	0 - 40°C / 32 - 104°F

\*Dimensions and specifications are subject to change without notice.