


Floor Scale, Mild Steel



Features:

- Heavy-duty industrial design
- Rigid steel channel frame
- Pre-trimmed corners
- Threaded eyebolt holes for easy lifting
- Powder Coating

Complete Set Includes:

- IP67 alloy steel load cells 563YH, OIML MAA & NTEP certified
- 4 swivel mild steel feet AMF with removable rubber base
- 2 eyebolts
- 1 IP67 aluminum junction box J04EA-16
- 1 level bubble

DIMENSIONS

PART NUMBER	RATED CAPACITY	DIVISION	LOAD CELL CAPACITY	SIZE IN INCHES (W x L x H)	WEIGHT	DECK PLATE THICKNESS
Painted Mild Steel						
FSP3×3-500kg	500kg	0.1kg	563YH-300kg	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP3×3-1t	1t	0.2kg	563YH-500kg	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP3×3-2.5t	2.5t	0.5kg	563YH-1t	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP3×3-1Klb	1Klb	0.2lb	563YH-500lb	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP3×3-2Klb	2Klb	0.5lb	563YH-1Klb	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP3×3-5Klb	5Klb	1lb	563YH-2.5Klb	36"×36"×4"	72kg / 159 lb	0.20" / 5mm
FSP4×4-500kg	500kg	0.1kg	563YH-300kg	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-1t	1t	0.2kg	563YH-500kg	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-2.5t	2.5t	0.5kg	563YH-1t	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-5t	5t	1kg	563YH-2t	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-1Klb	1Klb	0.2lb	563YH-500lb	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-2Klb	2Klb	0.5lb	563YH-1Klb	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-5Klb	5Klb	1lb	563YH-2.5Klb	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP4×4-10Klb	10Klb	2lb	563YH-4Klb	48"×48"×4"	120kg/265 lb	0.20" / 5mm
FSP5×5-2.5t	2.5t	0.5kg	563YH-1t	59"×59"×4"	200kg/441 lb	0.24" / 6mm
FSP5×5-5t	5t	1kg	563YH-2t	59"×59"×4"	200kg/441 lb	0.24" / 6mm
FSP5×5-5Klb	5Klb	1lb	563YH-2.5Klb	59"×59"×4"	200kg/441 lb	0.24" / 6mm
FSP5×5-10Klb	10Klb	2lb	563YH-SE5Klb	59"×59"×4"	200kg/441 lb	0.24" / 6mm
FSP5×5-10Klb-LE	10Klb	2lb	563YH-5Klb	59"×59"×5"	210kg/463 lb	0.24" / 6mm
FSP4×6-2.5t	2.5t	0.5kg	563YH-1t	48"×72"×4"	180kg/397 lb	0.24" / 6mm
FSP4×6-5t	5t	1kg	563YH-2t	48"×72"×4"	180kg/397 lb	0.24" / 6mm
FSP4×6-5Klb	5Klb	1lb	563YH-2.5Klb	48"×72"×4"	180kg/397 lb	0.24" / 6mm
FSP4×6-10Klb	10Klb	2lb	563YH-SE5Klb	48"×72"×4"	180kg/397 lb	0.24" / 6mm
FSP5×7-2.5t	2.5t	0.5kg	563YH-1t	59"×84"×4"	260kg/573 lb	0.24" / 6mm
FSP5×7-5t	5t	1kg	563YH-2t	59"×84"×4"	260kg/573 lb	0.24" / 6mm
FSP5×7-5Klb	5Klb	1lb	563YH-2.5Klb	59"×84"×4"	260kg/573 lb	0.24" / 6mm
FSP5×7-10Klb	10Klb	2lb	563YH-SE5Klb	59"×84"×4"	260kg/573 lb	0.24" / 6mm
Hot Dip Galvanized Mild Steel						
FSP4×4-5Klb-GI	5Klb	1lb	563YH-2.5Klb	48"×48"×4"	138kg/304 lb	0.20" / 5mm

OPTIONAL ACCESSORIES

- Indicators (page 157/158)
- Ramps-17 (page 181)
- Bumper Guards (page 182)
- Scale Base Mounting Plate (page 189)



Measurement Canada Approval for
- 3X3-5Klb - 4X4-5Klb - 5X5-5Klb



NTEP 1:5 000 Class III Approval for
- 3X3-1Klb - 4X4-1Klb - 5X5-1Klb
- 3X3-2Klb - 4X4-2Klb - 5X5-2Klb
- 3X3-5Klb - 4X4-5Klb - 5X5-5Klb
- 3X3-10Klb - 4X4-10Klb - 5X5-10Klb