


247AA; 247AS



Aluminum / Stainless Steel

FORCE MEASUREMENT



DIMENSIONS

RATED CAPACITY	C1	C2	H	H1	T1	T2
247AA:						
kg/mm						
1-20	20.0	15.0	11.0	4.0	M3	M3 Depth5.0
lb/inches (conversion of above dimensions)						
2.20-44.09	0.79	0.59	0.43	0.16	M3	M3 Depth0.20
247AS:						
kg/mm						
30-200	20.0	15.0	11.0	4.0	M3	M3 Depth5.0
500-1,000	25.4	18.0	15.0	5.0	M5	M4 Depth7.0
5,000	40.0	32.0	25.0	8.0	M12	M4 Depth6.0
lb/inches (conversion of above dimensions)						
66.14-440.92	0.79	0.59	0.43	0.16	M3	M3 Depth0.20
1,102.3-2,204.6	1.00	0.71	0.59	0.20	M5	M4 Depth0.28
11,023.1	1.57	1.26	0.98	0.31	M12	M4 Depth0.24

SPECIFICATIONS


Full Scale Output	Cap. ≤ 30kg: 1.0 mV/V ± 20%;	Recommended Excitation	10V (15V Maximum)
	Cap. ≥ 50kg: 1.5 mV/V ± 20%		Insulation Resistance
Zero Balance	± 0.03 mV/V	Nominal Temperature Range	-10°C to 40°C / 14°F to 104°F
Non-linearity	< ± 0.5%	Safe Overload	150% of full scale
Repeatability	< ± 0.3%	Breaking Overload	300% of full scale
Hysteresis Error	< ± 0.5%	Seal Type / IP Rating	Environmentally Sealed / IP66
Creep in 30 min.	< ± 0.5%	Cable Color Code	Exc+ Red Exc- Black
Input Resistance	375 Ω ± 25		Sig+ Green Sig- White
Output Resistance	350 Ω ± 3		Shield Bare
Element Material	Cap. ≤ 20kg: Aluminum, Clear Anodized Cap. ≥ 30kg: 17-4PH Stainless Steel		

PART NUMBER*

Rated Capacity	Part No.	Weight Approx. (kg)
1kg	247AA-1kg	0.07
2kg	247AA-2kg	0.07
5kg	247AA-5kg	0.07
10kg	247AA-10kg	0.07
20kg	247AA-20kg	0.07
30kg	247AS-30kg	0.07
50kg	247AS-50kg	0.07
100kg	247AS-100kg	0.07
150kg	247AS-150kg	0.07
200kg	247AS-200kg	0.11
500kg	247AS-500kg	0.11
1t	247AS-1t	0.11
5t	247AS-5t	0.21

* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

APPLICATION EXAMPLES



All product specifications, statements, information and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all conditions. It is the customer's responsibility to validate that a particular product with the properties described in the product specifications is suitable for use in their applications. Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge of product information at the time a publication was made, but are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another manufacturer.

Any use of product outside of specifications or any storage or installation inconsistent with product guidance voids and warranty.

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by ANYLOAD with reference to the use of ANYLOAD's products produces no obligation or liability for the advice given or results obtained.

Although ANYLOAD designs and manufactures its products to the most stringent quality and safety standards, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that ANYLOAD makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process. Although all product - related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required. Please contact authorized ANYLOAD personnel to obtain special terms and conditions regarding products designed for such applications or otherwise satisfy specific safety requirements.