



### DIMENSIONS

RATED CAPACITY	C1	C2	H	L	L1	L2	L3	L4	W	W1	W2	T
<b>kg/mm</b>												
125-250	-	9	25	110	54	57	33	10	21	25	2.5	M10
500-1,000	-	11	32	125	63	61.5	38	13	29	-	-	M12
2,500-5,000	21	21	50	190	99.5	88	60	20	46	-	-	-
10,000	26	26	66	227	117	117	60	25	50	-	-	-
<b>lb/inches</b> (conversion of above dimensions)												
276-551	-	0.35	0.98	4.33	2.13	2.24	1.30	0.39	0.83	0.98	0.10	M10
1,102-2,205	-	0.43	1.26	4.92	2.48	2.42	1.50	0.51	1.14	-	-	M12
5,512-11,023	0.83	0.83	1.97	7.48	3.92	3.46	2.36	0.79	1.81	-	-	-
22,046	1.02	1.02	2.60	8.94	4.61	4.61	2.36	0.98	1.97	-	-	-

### SPECIFICATIONS

<b>Full Scale Output</b>	125-500kg, 10t: 2.2 mV/V ± 0.25% 1-5t: 2.2 mV/V ± 0.05%	<b>Recommended Excitation</b>	10V (15V Maximum)
<b>Zero Balance</b>	± 0.02 mV/V	<b>Insulation Resistance</b>	>2 [ 50V DC ] GΩ
<b>Non-linearity</b>	< ± 0.017%	<b>Compensated Temperature Range</b>	-10°C to 50°C / 14°F to 122°F
<b>Repeatability</b>	< ± 0.017%	<b>Safe Overload</b>	150% of full scale
<b>Hysteresis Error</b>	< ± 0.017%	<b>Breaking Overload</b>	300% of full scale
<b>Creep in 30 min.</b>	< ± 0.023%	<b>Seal Type / IP Rating</b>	Cap. ≤ 250kg: Environmentally Sealed / IP66 Cap. ≥ 500kg: Environmentally Sealed / IP67
<b>Input Resistance</b>	385Ω ± 15	<b>Cable Color Code</b>	Exc+ Red    Exc- Black Sig+ Green    Sig- White Shield Bare
<b>Output Resistance</b>	350Ω ± 3		
<b>Element Material</b>	Alloy Steel, Nickel Plated		

### PART NUMBER\*

Rated Capacity	Part No.	Weight Approx. (kg)
125kg	563YHFK-125kg	0.7
250kg	563YHFK-250kg	0.7
500kg	563YHFK-500kg	1.0
1t	563YHFK-1t	1.0
2.5t	563YHFK-2.5t	2.8
5t	563YHFK-5t	3.0
10t	563YHFK-10t	4.9

\* ATEX, FM, IECEx approved versions carry the "-Ex" suffix.

### INTERCHANGEABLE REFERENCE

ANYLOAD Part No.	Kelba Model
563YHFK-125kg	KA125N
563YHFK-250kg	KA250N
563YHFK-500kg	KA500N
563YHFK-1t	KA1000N
563YHFK-2.5t	KA2500N
563YHFK-5t	KA5000N
563YHFK-10t	KA10000N

125kg-1t: NTEP 1:5 000 Class III, Single Cell;  
NTEP 1:9 500 Class III, Multiple Cell  
2.5t-5t: NTEP 1:6 000 Class III, Single Cell;  
NTEP 1:10 000 Class III, Multiple Cell

500kg-2.5t: OIML MAA C5, Y=26 000;  
5t-10t: OIML MAA C6, Y=8 500  
For further available P/N's & specifications per NTEP/OIML classes, please contact us.

All product specifications, statements, information and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. The customer is responsible for checking and verifying the extent to which the Information contained in this publication is applicable to an order at the time the order is placed. All Information given herein is believed to be accurate and reliable, but it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all conditions. It is the customer's responsibility to validate that a particular product with the properties described in the product specifications is suitable for use in their applications. Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge of product information at the time a publication was made, but are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another manufacturer.

Any use of product outside of specifications or any storage or installation inconsistent with product guidance voids and warranty.

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by ANYLOAD with reference to the use of ANYLOAD's products produces no obligation or liability for the advice given or results obtained.

Although ANYLOAD designs and manufactures its products to the most stringent quality and safety standards, isolated component failures may still occur. Accordingly, customer applications which require a high degree of reliability or safety should employ suitable designs or other safeguards in order to ensure that the failure of an electrical component does not result in a risk of personal injury or property damage.

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services or deliverables for use in high risk applications including medical life support, medical device, direct physical patient contact, water treatment, nuclear facilities, weapon systems, mass and air transportation control, flammable environments, or any other potentially life critical uses. Customer understands and agrees that ANYLOAD makes no assurances that the products, services or deliverables are suitable for any high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process. Although all product - related warnings, cautions and notes must be observed, the customer should not assume that all safety measures are indicated or that other measures may not be required. Please contact authorized ANYLOAD personnel to obtain special terms and conditions regarding products designed for such applications or otherwise satisfy specific safety requirements.