Quadro Set 3; Quadro Set 5

Load Cell Certifications:

Features:

- NTEP certified load cells from 250lb-20Klb
- OIML certified load cells from 500kg-10t & 10K-20Klb (QS3); OIML certified load cells from 1Klb-10Klb (QS5);
- CE , RoHS and ExNepsi certified load cells
- Full Scale Output: 2mV/V ± 0.25% (QS3); 3mV/V ± 0.25% (QS5);
- Junction box is equipped with integrated resistor networks
- Cable is coloured in accordance to the ANYLOAD color code

Complete Set:

- 4 pcs x Stainless steel single ended shear beam load cells (563YS or 563YS30)
- 4 pcs x Stainless steel load cell spacers (SPACERSS)
- 4 pcs x Stainless steel mounting feet (AMFSS)
- 1 pc x Aluminum junction box (J04EA-16 or J04SA-16)
- 1 pc x 20m (65 feet) PVC cable (CB4-5.1-20m)

PART NUMBER

QS3-SA-16 (563YS, J04SA-16)

Load Cell Capacity	Part No.	Weight Approx. (kg)
500lb	QS3-SA-16-500lb	7.6
1Klb	QS3-SA-16-1Klb	7.6
2.5Klb	QS3-SA-16-2.5Klb	7.6
4Klb	QS3-SA-16-4Klb	7.6
SE5Klb	QS3-SA-16-SE5Klb	7.6
5Klb	QS3-SA-16-5Klb	11.4
10Klb	QS3-SA-16-10Klb	11.4

QS3-16 (563YS, J04EA-16)

Load Cell Capacity	Part No.	Weight Approx. (kg)
250kg	QS3-16-250kg	7.6
500kg	QS3-16-500kg	7.6
1t	QS3-16-1t	7.6
2t	QS3-16-2t	7.6
3t	QS3-16-3t	11.4
5t	QS3-16-5t	11.4
500lb	QS3-16-500lb	7.6
1Klb	QS3-16-1Klb	7.6
2.5Klb	QS3-16-2.5Klb	7.6
4Klb	QS3-16-4Klb	7.6
SE5Klb	QS3-16-SE5Klb	7.6
5Klb	QS3-16-5Klb	11.4
10Klb	QS3-16-10Klb	11.4

PART NUMBER

QS5-SA-16 (563YS30, J04SA-16)

Load Cell Capacity	Part No.	Shipping Weight Approx. (kg)
500lb	QS5-GS-SA-16-500lb	7.6
1Klb	QS5-SA-16-1Klb	7.6
2.5Klb	QS5-SA-16-2.5Klb	7.6
4Klb	QS5-SA-16-4Klb	7.6
SE5Klb	QS5-SA-16-SE5Klb	7.6
5Klb	QS5-SA-16-5Klb	11.4
10Klb	QS5-SA-16-10Klb	11.4

QS5-16 (563YS30, J04EA-16)

Load Cell Capacity	Part No.	Shipping Weight Approx. (kg)
500lb	QS5-GS-16-500lb	7.6
1Klb	QS5-16-1Klb	7.6
2.5Klb	QS5-16-2.5Klb	7.6
4Klb	QS5-16-4Klb	7.6
SE5Klb	QS5-16-SE5Klb	7.6
5Klb	QS5-16-5Klb	11.4
10Klb	QS5-16-10Klb	11.4

© 2024 ANYLOAD V2 dimensions and specifications subject to change without notice