

Axle Weigh Pad



SPECIFICATIONS	
Display	6 Digit FSTN LCD (Height 11mm / 1/2in) & LED Backlight
Operating Switch	2 Capacitive Touch Buttons
Front Cover Material	Polycarbonate
Housing material	Aluminum, Hammer-Tone Powder Coating
Battery	Rechargeable 18650 Li-ion with PCM (Protection Circuit module)
Charger	100 to 240VAC, 60Hz
Operating Time	Continuous use: Approx. up to 600 hours
Operating Temperature	-20°C to 60°C / -4°F to 140°F
Operating Humidity	85% R.H. (No Condensation)

Features:

- Highly durable powder-coated aluminum chassis
- Up to 600 hours of continuous use per charge battery replaceable & rechargeable
- Zigbee wireless communication for reliable cable-free setup
- IP68 Waterproof with operating temperature range of -20°C to 60°C / -4°F to 140°F for all-weather usage
- Weigh-in-motion (WIM) feature on AXA-8
- 6-digit LCD with LED backlight for clear weight display
- Rugged polycarbonate front cover for enhanced impact resistance
- Compact and portable; ideal for mobile axle weighing applications

Portable wireless indicator AN560:


- E-ink Display With Backlight
- IP67 (Closed)
- Rechargeable Battery 600 Hours
- 24-Key Keypad
- Built-in Thermal Printer
- Pairs Up To 8 AXA Pads



(Order separately. Check AN560 data sheet for more details)

Part Number	Model	Capacity	Division	Pad Size	Overall Dimension	Height	Self Weight (Approx.)
AXA-3-0.5t	AXA-3	0.5t (1Klb)	0.2kg (0.5lb)	12 x 12in (305 x 305mm)	17.5 x 14.5in (444 x 368mm)	1.22in (31mm)	5.8kg (12.8lb) ramp included
AXA-3-1t		1t (2Klb)	0.5kg (1lb)				
AXA-3-2t		2t (4Klb)	1kg (2lb)				
AXA-5-3t	AXA-5	3t (6Klb)	1kg (2lb)	19.7 x 14.6in (500 x 370mm)	22.2 x 23.9in (563 x 606mm)	1.42in (36mm)	16kg (35.3lb) ramp included
AXA-5-5t		5t (10Klb)	2kg (5lb)				
AXA-8-10t	AXA-8	10t (22Klb)	10kg (20lb)	31.5 x 19.7in (800 x 500mm)	34.5 x 35.4in (876 x 900mm)	1.42in (36mm)	25kg (55lb) ramp included
AXA-8-15t		15t (33Klb)	10kg (20lb)				
AXA-8-20t		20t (44Klb)	10kg (20lb)				

Accessories: Extension Pad



To be ordered separately, Part Number: AXA-8-EXT-30

AXLE WEIGH PAD

Product Datasheet Disclaimer

Information Changes:

All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:


Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

 **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.