

## LCD Industrial Weight Indicator



Measurement  
Canada



## Keyboard Configuration



## SPECIFICATIONS

<b>Power Supply</b>	AC adaptor, 100 VAC to 240 VAC, 50~60 Hz Built-in 10,000 mAH internal rechargeable lithium battery
<b>Power Consumption</b>	120 VAC @ 0.1A / 12 VDC @ 0.5 A (10 WAC / 5 W DC) typical
<b>Excitation Voltage</b>	5 VDC ± 5%
<b>Number of Load Cells</b>	Up to 4 x 350 Ω; 8 x 700 Ω
<b>Input Range</b>	Up to 3.9 mV/V
<b>Sample Rate</b>	80 Hz
<b>Resolution</b>	1,000,000 internal count, with 24 bits resolution
<b>Division</b>	Legal for trade 10,000 d / 20,000 d
<b>Tare Range</b>	100% Full Scale NTEP / MC / OIML
<b>Communicate Interface</b>	2 x RS-232C
<b>Working Humidity</b>	20% RH to 90% RH
<b>Working Temperature</b>	-10°C to 50°C / 15°F to 120°F
<b>Dimensions (W x H x D)</b>	9.1" x 7.4" x 3.0" (231 x 196 x 76 mm) base included

## PART NUMBER


Part No.	Power Supply	Weight Approx. (kg)
815BS-B2-21E.....External.....	External.....	2.5

## Features:

- 1.0", 6 digits, 7 segments, LCD display
- Tri color backlight: green, red and amber
- Indication of up to four units of measurements: kg, lb, oz and g
- Indication of gross, net and tare
- Indication of stability and centre of zero
- Easy wiring screw terminals
- Weight, peak, set point, and piece counting
- Password protected setup and calibration menu
- Physical and electronic sealing with audit trail function
- Advance analogue, average and digital filtering
- Two independent RS-232 communication ports
- UL approved external wall adapter
- Built in lithium battery with internal charger
- Weatherproof stainless steel enclosure, NEMA4X / IP66
- Breather vent to avoid condensation inside

## Approvals:

- NTEP: Class III / IIIL 10,000 d
- Measurement Canada: Class III / IIIHD 10,000 d / 20,000 d



## DIMENSIONS

L	7.7in (196mm)	H	4.9in (125mm)	W	2.3in (58mm)
L1	8.0in (202mm)	H1	5.9in (149mm)	W1	3.0in (76mm)
L2	9.1in (231mm)	H1	7.4in (188mm)	W2	0.3in (7mm)
L3	4.9in (125mm)	C	1.6in (40mm)		
L4	1.2in (30mm)	C1	0.4in (9mm)		

# Product Datasheet Disclaimer

## Information Changes:

All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

## Accuracy and Reliability:

While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

## Laboratory Conditions:

Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

## Interchangeability:

Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

## Warranty Voidance:

Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

## Intended Use:

The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

## Component Failures:

Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

## High-Risk Applications:

Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

## Safety Measures:

All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

## California Proposition 65:

 **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.