Description:

The 101NHM2 Tension Weigh Module Kit is a robust and reliable solution designed for high-accuracy tension weighing applications. The kit is a complete package with all required components, ensuring ease of installation. Assembling the 101NH S-beam load cell with 101NHM2 mounts, this kit provides exceptional performance in demanding environments, making it ideal for suspended tanks and hoppers, especially in concrete batching plants.



Load Cell Certifications:

Features:

- Compatible with 101NH S-beam load cell
- Constructed from durable alloy steel for long-lasting use
- Capacities: 50lb to 10,000lb (per module)
- NTEP-certified load cells available from 100lb to 20,000lb for legal-for-trade applications
- OIML-certified load cells from 200kg to 10t for international standards compliance
- CE, RoHS, and Ex certified for a wide range of industrial settings
- Grounding strap included to divert all currents, ensuring the load cell is protected
- Engineered for precise tension loading applications

PART NUMBER

Load Cell Capacity	Part No.	Weight Approx. (kg/lb)
50lb	MK4-101NHM2-50lb-S	2.8/6.2
100lb	MK4-101NHM2-100lb-S	2.8/6.2
200lb	MK4-101NHM2-200lb-S	2.8/6.2
250lb	MK4-101NHM2-250lb-S	2.8/6.2
500lb	MK4-101NHM2-500lb-S	6.8/15.0
750lb	MK4-101NHM2-750lb-S	6.8/15.0
1Klb	MK4-101NHM2-1Klb-S	6.8/15.0
1.5Klb	MK4-101NHM2-1.5Klb-S	6.8/15.0
2Klb	MK4-101NHM2-2Klb-S	6.8/15.0
5Klb	MK4-101NHM2-5Klb-S	14.0/30.9
10Klb	MK4-101NHM2-E-10Klb-S	35.2/77.6

Complete Set Includes:

- (4 pcs) Four 101NH Alloy Steel S-beam load cells
- (4 pcs) Four 101NHM2 Alloy Steel weigh modules
- (1 pcs) One J04SA-16 water-resistant junction box
- (1 roll) 65ft (20m) cable, 4-wire PVC cable with copper braid & foil shielding (CB4-5.1-20m)

© 2026 ANYLOAD V1 dimensions and specifications subject to change without notice

Product Datasheet Disclaimer

Information Changes:
All product specifications, statements, information, and data (collectively, the "Information") in this catalog or made available elsewhere by ANYLOAD are subject to change. Customers must verify the applicability of the Information at the time of order placement.

Accuracy and Reliability:
While all Information is believed to be accurate and reliable, it is presented without guarantee, warranty, or responsibility of any kind, expressed or implied.

Laboratory Conditions:
Data listed in the datasheet is produced within controlled laboratory settings and may not be reproducible without exact replication of all metrological conditions. Users must validate that a product with the described properties is suitable for their applications.

Interchangeability:
Statements of interchangeability with other manufacturers are based on ANYLOAD's knowledge at the time of publication and are not intended to constitute any warranty concerning the substitutability of an ANYLOAD product with one made by another Manufacturer.

Warranty Voidance:
Any use of the product outside of specifications or any storage or installation inconsistent with product guidance voids any warranty.

Intended Use:
The information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. ANYLOAD provides technical advice without obligation or liability for the advice given or results obtained.

Component Failures:
Although ANYLOAD designs and manufactures its products to stringent quality and safety standards, isolated component failures may still occur. Applications requiring high reliability or safety should employ suitable designs or safeguards to ensure that component failure does not result in personal injury or property damage.

High-Risk Applications:
Unless specifically agreed to in writing, ANYLOAD has not tested or certified its products, services, or deliverables for use in high-risk applications (e.g., medical life support, nuclear facilities, weapon systems). ANYLOAD makes no assurances that the products are suitable for high-risk uses. Under no circumstances does ANYLOAD warrant or guarantee suitability for any customer design or manufacturing process.

Contact authorized ANYLOAD personnel for special terms and conditions regarding products designed for specific safety requirements.

Safety Measures:
All product-related warnings, cautions, and notes must be observed. Customers should not assume that all safety measures are indicated or that other measures may not be required.

California Proposition 65:

⚠ **WARNING:** Some products manufactured or distributed by ANYLOAD may contain trace amounts of chemicals known to the State of California to cause cancer, birth defects, or other reproductive harm. These substances are present in minimal quantities and are typically encapsulated within our products. This warning is provided to enable you to make informed decisions as a consumer.

© 2026 ANYLOAD V1 dimensions and specifications subject to change without notice